

L41 Self assessment questions in fuels, furnace and refractory

ENOUGH SELF EVALUATION QUESTIONS ARE GIVEN IN THE WEB LECTURES. HERE ARE ADDITIONAL QUESTIONS. ANSWERS MAY BE FOUND IN LECTURES

- 1) Which of the following is not a property of ceramic fibre insulation
 - a) Low thermal conductivity
 - b) Light weight
 - c) High heat capacity
 - d) Thermal shock resistant

- 2) The waste heat recovery equipment in a combustion system will be more economical when the exit flue gases are at a temperature of
 - a) 200°C
 - b) 400°C
 - c) 600°C
 - d) 800°C

- 3) Which of the following will not conserve energy in a furnace
 - a) Preheating combustion air
 - b) Charge preheating
 - c) Optimizing excess air
 - d) Addition of more burners

- 4) What is the major energy loss in an oil fired reheating furnace?
 - a) Loss due to evaporation of moisture in fuel
 - b) Skin losses
 - c) Sensible heat loss in flue gas
 - d) Heat loss through openings

- 5) The coefficient of thermal expansion of refractory material should be
 - a) Very high
 - b) High
 - c) Medium
 - d) Low

- 6) Alumina is a..... type of refractory
- a) Acid
 - b) Neutral
 - c) Basic
 - d) None of the above
- 7) Regenerators are widely used in
- a) Reheating furnaces
 - b) Heat treatment furnaces
 - c) Baking ovens
 - d) Glass melting furnaces
- 8) Heat loss through openings in furnaces is directly proportional to
- a) Fourth power of absolute temperature
 - b) Square of absolute temperature
 - c) Absolute temperature
 - d) Fourth power of temperature
- 9) For a coal containing 80% C and 6% ash, the coke produced per ton of coal would be
- a) 750 kg with 8% ash
 - b) 800 kg with 8% ash
 - c) 650kg with 8.8% ash
 - d) 600 kg with 9% ash
- 10) The refractory lining for soaking pits must not have
- a) Resistance to iron oxide attack
 - b) Low abrasion resistance
 - c) Good load bearing capacity
 - d) High abrasion resistance
- 11) The refractory materials for Hall-Heroult cell should be resistant to
- a) Abrasion
 - b) thermal spalling

- c) Molten aluminum attack
- d) Mechanical shock

- 12) The sensible heat in flue gases is 14000kJ/kg fuel. If the efficiency limit and the relative efficiency of the regenerator is 87% and 80% respectively, then heat recovered in preheated air is
- a) 11200kj
 - b) 9744kj
 - c) 12180kj
 - d) 11690kj

- 13) In radiant heat exchange between two black surfaces the composite geometrical factor (F_{BR}) due to refractory surface is
- a) $F_{BR} = 0.5(1 + F_B)$ when $A_2/A_1 = 1$
 - b) $F_{BR} = 0.75$ when $A_2/A_1 = 1$ and $F_B = 0.5$
 - c) $F_{BR} = 0.5$ when $A_2/A_1 = 1$ and $F_B = 0$
 - d) $F_{BR} \rightarrow 1$ when $A_2/A_1 = \infty$

- 14) Why adiabatic flame temperature is greater than the actual flame temperature? Explain

- 15) Explain the difference between the following pairs

- i) Natural draft and forced draft
- ii) Carbonization and gasification
- iii) Primary and secondary air
- iv) Luminous and non-luminous flame
- v) Lignite and anthracite.

- 16) A fuel oil of composition 84.9% C, 11.4% H, 3.2% S, 0.4% O and 0.1 % ash is burnt with 20% excess air. Assume complete combustion. The amount of air is closed to

- a) 1400kg
- b) 1672kg
- c) 1500kg
- d) 1650kg

- 17) The ultimate analysis of a coal(moist basis in %): C 69.8 , H 4.6 , N 1.4, O 8.5, S 2.5, H₂O 4.5 and ash 8.7. The gross calorific value, moist basis, is 29920 KJ/Kg. Calculate, by means of the Dulong formula, the gross calorific value, moist basis, of the coal.

18) The proximate analysis of coal is: Moisture 2.4%, Volatile Matter 29.4%, Fixed Carbon 58%, Ash 9.7% and Sulphur 0.5%. Its gross calorific value is 7650 Kcal/Kg. Calculate proximate analysis and calorific value on

a) Moisture free basis

19) A furnace is heated by combusting a gaseous fuel of composition 29% CO, 9% CO₂, 16% H₂ and 46% N₂ with dry air. The Orsat analysis of products of combustion (POC) is 15% CO₂, 7% O₂ and 78 %N₂.

i) volume of POC at NTP in m³ is close to

- A. 2.53
- B. 2.60
- C. 2.57
- D. 2.59

ii) Volume of air at NTP in m³ is close to

- A. 1.916
- B. 1.876
- C. 1.098
- D. 1.076

iii) Percent excess air is close to

- A. 70
- B. 79
- C. 82
- D. 78

20) A pitot tube is installed at the centre of a pipe of diameter 0.3m. The pipe carries air at 70°C. Air is flowing at 745 mm Hg gauge pressure. Pitot tube measures a pressure difference of 50 mm water. Calculate flow rate of air in pipe. Assume pitot coefficient unity.