

References

Books

- Agrawal, P. and Shrikhande, M. (2006), "Earthquake resistant design of structures", Prentice Hall of India, Inc.
- Chopra, A.K. (2007), "Dynamics of structures: Theory and application to earthquake engineering", 2nd edition, Prentice Hall of India.
- Chowdhary, I. and Dasgupta, S.P. (2009). "Dynamics of structure and foundation – A unified approach : 2 Applications", CRC Press, Balkema.
- Clough, R. W. and Penzien, J. (1993). "Dynamics of structures", McGraw Hill, Inc., New York.
- Datta, T. K. (2010). "Seismic analysis of structures", John Wiley & Sons (Asia) Pte Ltd. Singapore.
- Hart, G. C. and Wong, K. (2000). "Structural dynamics for structural engineers", John Wiley & Sons, Inc., New York.
- Kramer, S. L. (1996), "Geotechnical earthquake engineering", Prentice Hall, 2007, ISBN 81-317-0718-0.
- Lay, T. and Wallace, T.C.,(1995) "Modern global seismology", Academic press, 1995, ISBN 0-12-732870-X.
- Naeim, F. and Kelly, J. M. (1999), "Design of seismic isolated structures: From theory to practice", John Wiley and Sons, Inc., New York, USA.
- Reiter L., (1989), "Earthquake hazard analysis: Issues and insights", Columbia University Press.
- Wolf, J.P. (1985). "Dynamic soil-structure interaction", Prentice Hall, Englewood Cliffs, New Jersey.

Research Papers

- Ambraseys, N.N., (1996), “The prediction of earthquake peak ground acceleration in Europe”, *Earthquake Engineering & Structural Dynamics*, Vol. 24, pp. 467 – 490.
- Kumar, A., Mittal, H and Sachdeva, R. 2012, “Indian strong motion instrumentation network”, *Seismological Research Letters*, Vol. 83(1), pp. 59-66.
- ATC, 1996, “Seismic evaluation and retrofit of concrete buildings”, *ATC-40 Report, Volumes 1 and 2, Applied Technology Council*, Redwood City, California.
- Atkinson, G.M. and Boore, D.M., (2006), “Earthquake ground motion prediction equations for eastern North America”, *Bulletin of Seismological Society of America*, Vol. 96(6), 2181-2205.
- Bakir, B.S., Ozkan, M.Y. and Ciliz, S. (2002). “Effects of basin edge on the distribution of damage in 1995 Dinar, Turkey earthquake”, *Soil Dynamics and Earthquake Engineering*, Vol. 22, 335-345.
- Bard, P.Y. and Bouchon, M. (1980a). “The seismic response of sediment-filled valleys. Part 1. The case of incident SH waves”, *Bulletin of Seismological Society of America*, Vol. 70, 1263-1286.
- Bard, P.Y. and Bouchon, M. (1980b). “The seismic response of sediment-filled valleys. Part 2. The case of incident P and SV waves”, *Bulletin of Seismological Society of America*, Vol. 70, 1921-1941.
- Boore, D.M., Joyner, W.B. and Fumal, T.E. (1997), “Equations for estimating horizontal response spectra and peak acceleration from Western North American earthquakes: A summary of work”, *Seismological Research Letters*, Vol. 68, No. 1, pp.128-153.
- Boore, D.M., (2001), “Effect of baseline corrections on displacements and response spectra for several recordings of the 1999 Chi-Chi”, Taiwan earthquake, *Bulletin of the Seismological Society of America*, Vol. 91, 5, pp. 1199–1211.
- Boore D.M. and Bommer, J.J (2005), “Processing of strong-motion accelerograms: Needs, options and consequences”, *Soil Dynamics and Earthquake Engineering*, Vol. 25, pp. 93–115.

- Campbell, K.W. and Bozorgnia, Y. (2008), “NGA ground motion model for the geometric mean horizontal component of PGA, PGV, PGD and 5% damped linear elastic response spectra for periods ranging from 0.01 to 10s”, *Earthquake Spectra*, Vol. 24(1), pp 139-172.
- Campbell, W.K. (1997), “Empirical near-source attenuation relationships for horizontal and vertical components of peak ground acceleration, peak ground velocity and pseudo-absolute acceleration response spectra”, *Seismological Research Letters*, Vol. 68, No. 1, pp.154-179.
- Celebi, M. (1987). “Topographical and geological amplifications determined from strong-motion and aftershock records of the 3 March 1985 Chile earthquake”, *Bulletin of Seismological Society of America*, Vol. 77, 1147-1167.
- Chiou, B.J. and Youngs, R., (2008), “An NGA model for average horizontal component of peak ground motion and response spectra”, *Earthquake Spectra*, Vol. 24(1), pp 173-216.
- Clark, P.W., Aiken, I.D. and Kelly, J.M. (1997) “Ongoing studies of the foothill communities law and justice center”, *Proceedings of Structures Congress XV*, April 13-16, Portland, Oregon, USA.
- Computers and Structures SAP-2000: “Three dimensional static and dynamic finite element analysis and design of structures”, *Computers and Structures Inc.*, Berkeley, California, USA.
- Cornell, C.A., (1968), “Engineering seismic risk analysis”, *Bulletin of Seismological society of America*, Vol. 58(5), pp. 583-606.
- Geli, L., Bard, P. Y. and Jullien, B. (1988). “The effect of topography on earthquake ground motion: a review and new results”, *Bulletin of Seismological society of America*, Vol. 78, 42-63.
- Gent A. N. (1964), “Elastic stability of rubber compression springs”, *Journal of Mechanical Engineering Science*, Vol. 4(6), 318-326.
- Graves, R. W., Pitarka, A. and Somerville, P. G. (1998), “Ground motion amplification in the santa monica area: Effects of shallow basin edge structure”, *Bulletin of Seismological society of America*, Vol. 88, pp. 1224-1242.

- Gueraud, R., Noel-Leroux, J.P., Livolant, M. and Michalopoulos, A.P. (1985) “Seismic isolation using sliding-elastomer bearing pads”, *Nuclear Engineering and Design*, Vol. 84(3), 363-377.
- Hanks, T. and Kanamori, H. (1979). “A moment magnitude scale”, *Journal of Geophysical Research*, Vol. 84(B5), pp. 0148-0227.
- Hatyama, K., Matsunami, K., Iwata, T. And Irikura, K. (1995). “Variability of site response in seattle”, Washington, BSSA, Vol. 90, pp. 237-1250.
- Ibrahim, R.A. (2008), “Recent advances in nonlinear passive vibration isolators”, *Journal of Sound and Vibration*, Vol. 314(3-5), pp. 371-452.
- Idriss, I.M., (2008), “An NGA empirical model for estimating the horizontal spectral values generated by shallow crustal earthquakes”, *Earthquake Spectra*, Vol. 24(1), pp. 217-255.
- Jangid, R.S. (2005) “Optimum friction pendulum system for near-fault motions”, *Engineering Structures*, USA, Vol. 27, pp. 349-359.
- Jangid, R.S. (2006) “Seismic response of isolated bridges”, *Journal of Bridge Engineering*, ASCE, USA, Vol. 9, pp. 156-166.
- Jangid, R.S.(2008) “Stochastic response of bridges seismically isolated by friction pendulum system”, *Journal of Bridge Engineering*, ASCE, USA, Vol. 13, pp. 319-330.
- Jangid, R.S. (2010) “Stochastic response of building frames isolated by lead-rubber bearings”, *Structural Control and Health Monitoring*, Vol. 17, pp. 1-22.
- Jangid, R.S. and Datta, T.K. (1995) “Seismic behavior of base isolated building : A State-of-the-art review”, *Structures and Buildings*, 110(2), 186-203.
- Jangid, R.S. and Kelly, J.M. (2001) “Base isolation for near-fault motions”, *Earthquake Engineering and Structural Dynamics*, USA, Vol. 30, pp. 691-707.
- Jain, S.K., Roshan, A. D. Yadav, S, Srivastava, S and Basu, P.C., 2012, “Strong-motion data from structural response recorders in Indian earthquakes”, *Earthquake Spectra*, Vol. 28(1), pp. 77–103.

- Kawase, H. (1996). "The cause of the damage belt in Kobe: The Basin-edge effect, Constructive interference of the direct S-wave with the basin-induced diffracted/Rayleigh waves", *Seismological Research Letter*, Vol. 67, No.5, pp. 25-34.
- Kelly, J.M. (1986) "Aseismic base isolation: Review and bibliography", *Soil Dynamics and Earthquake Engineering*, Vol. 5(3), pp. 202-216.
- Kikuchi, M. and Aiken, I.D. (1997) "An analytical hysteresis model for elastomeric seismic isolation bearings", *Earthquake Engineering and Structural Dynamics*, Vol. 26(2), pp. 215-231.
- Koo, G.H., Lee, J.H., Yoo, B. and Ohtori, Y. (1999) "Evaluation of laminated rubber bearings for seismic isolation using modified macro-model with parameter equations of instantaneous apparent shear modulus", *Engineering Structures*, 21(7), 594-602.
- Kunde, M.C. and Jangid, R.S. (2003) "Seismic Behaviour of Isolated Bridges: A State-of-the-Art Review", *Electronic Journal of Structural Engineering*, Vol. 3, pp. 140-170.
- Kunde, M.C. and Jangid, R.S. (2006) "Effects of pier and deck flexibility on the seismic response of the isolated bridges", *Journal of Bridge Engineering*, ASCE, USA, Vol. 11, pp. 109-121.
- Malushte, S.R. and Whittaker, A.S. (2005) "Survey of past base isolation applications in nuclear power plants and challenges to industry/regulatory acceptance", *18th International Conference on Structural Mechanics and Reactor Technology*, August 7-12, Beijing, China.
- McGuire R.K., (1978), "Seismic ground motion parameter relations", *Journal of Geotechnical Engineering Division (ASCE)*, Vol. 104, pp. 481-490.
- Matsagar, V.A. and Jangid, R.S. (2004) "Influence of isolator characteristics on the response of base-isolated structures", *Engineering Structures*, Vol. 26(12), pp. 1735-1749.
- Matsagar, V.A. and Jangid, R.S. (2008) "Base isolation for seismic retrofitting of structures", *Practice Periodical on Structural Design and Construction (ASCE)*, Vol. 13(4), pp. 1-11.
- Mostaghel, N. and Khodaverdian, M. (1987) "Dynamics of resilient-friction base isolator (R-FBI)", *Earthquake Engineering and Structural Dynamics*, Vol. 15(3), pp. 379-390.

- Mostaghel, N. and Mortazavi, A.R. (1991) “An assessment of seismic draft code for resilient sliding isolators”, *Earthquake Engineering and Structural Dynamics*, Vol. 20(6), pp. 523-533.
- Narayan and Sharma (2004), “Effects of local geology on damage severity during Bhuj, India earthquake”, *13th World Conference on Earthquake Engineering, Vancouver, B.C., Canada*, August 1-6, 2004.
- Narayan, J.P. and Rao, P.V. (2003). “Two and half dimensional simulation of ridge effects on the ground motion characteristics”, *Pure and Applied Geophysics*, Vol. 160, pp. 1557-1571.
- Narayan, J.P. (2005). “Study of Basin-edge effects on the ground motion characteristics using 2.5-D modeling”, *Pure and Applied Geophysics.*, Vol. 162, pp. 273-289.
- Nigam, N. C. Jennings, P. C. (1969), “Calculation of response spectra from strong-motion earthquake records”, *Bulletin of the Seismological Society of America*, Vol. 59, No. 2, pp. 909-922.
- Panchal , V.R. and Jangid, R.S. (2008) “Variable friction pendulum system for seismic isolation of liquid storage tanks”, *Nuclear Engineering and Design*, USA, Vol. 238, pp. 1304-1315.
- Pisal, A.Y. (2006). “Effect of strong lateral discontinuity on ground motion characteristics and aggravation factor”, Mtech. Thesis, IIT Roorkee.
- Pitarka, A., Irikura, K. Iwata, T. and Sekiguchi, H. (1998). “Three-dimensional simulation of the near fault motion for the 1995 Hyogoken Nanbu (Kobe), Japan, earthquake”, *Bulletin of the Seismological Society of America*, Vol. 88, pp. 428-440.
- Robinson, W.H. (2000) “Seismic isolation of civil buildings in New Zealand”, *Progress in Structural Engineering and Materials*, Vol. 2(3), pp. 328-334.
- Roshan, A.D. and Basu, P.C., (2010), “Application of PSHA in low seismic region: A case study on NPP site in peninsular India”, *Nuclear Engineering and Design*, Vol. 240, Issue 10, pp. 3443-3454.

- Sadigh, K., Chang, C.Y., Egan, J.A., Makdisi, F. and Youngs, R.R., (1997), "Attenuation relations for shallow crustal earthquakes based on California strong motion data", *Seismological Research Letters*, Vol. 68(1), pp. 180-189.
- Sharpe, R. (2002) "Base isolation", *E-Conference on Indian Seismic Codes, January 26-February 8, National Information Centre of Earthquake Engineering, Indian Institute of Technology (IIT) Kanpur, Kanpur, India.*
- Shrimali, M.K. and Jangid, R.S. (2002) "A comparative study of performance of various isolation systems for liquid storage tanks", *International Journal of Structural Stability and Dynamics*, Vol. 2(4), pp. 573-591.
- Shrimali, M.K. and Jangid, R.S., (2003), "Seismic response of base-isolated liquid storage tanks", *Journal of Vibration and Control, USA*, Vol. 9, pp. 1201-1218.
- Simo, J.C. and Kelly, J.M. (1984), "The analysis of multi-layer elastomeric bearings", *Journal of Applied Mechanics (ASME)*, Vol. 51, pp. 256-262.
- Skinner, R.I., Kelly J.M. and Heine A.J. (1975), "Hysteretic dampers for earthquake resistant structures", *Earthquake Engineering and Structural Dynamics*, Vol. 3, No. 3, pp. 287-296.
- Stanton, J. and Roeder, C. (1991) "Advantages and limitations of base isolation", *Earthquake Spectra*, Vol. 7, No.2, pp. 301-324.
- Street, R. L. and Turcotte, F. T., (1977), "A study of northeastern North American spectral moments, magnitudes and intensities", *Bulletin of Seismological Society of America*, Vol. 67, pp. 599- 614.
- Takewaki, I. (2011), "Preliminary report of the 2011 of the Pacific Coast Tohoku earthquake", *Journal of Zhejiang University - SCIENCE A (Applied Physics and Engineering)*, Vol. 12, No. 5, pp. 327-334.
- Tsopelas, P.C., Constantinou, M.C. and Reinhorn, A.M. (1991), "3D-BASIS-M: Nonlinear dynamic analysis of multiple building base-isolated structures", *National Center for Earthquake Engineering Research, University at Buffalo*, Report No. NCEER-91-0014, Buffalo, New York, USA.

- Walters, M. (2003), "The seismic retrofit of the Oakland City Hall", *Proceedings of Strong Motion Instrumentation Program, May 22, Oakland, California, USA.*
- Wang, Y.P. (2002), "Fundamentals of seismic isolation", *International Training Program of Seismic Design of Building Structures*, Taipei, Taiwan. pp. 21-25,
- Wald , D. J., Quitoriano, V., Heaton, T. H. and Kanamori, H., 1999a, "Relationships between peak ground acceleration, peak ground velocity and Modified Mercalli intensity in California", *Earthquake Spectra*, Vol. 15, No. 3, pp. 557-564.
- Wen, Y.K. (1976), "Method for random vibration of hysteretic systems", *Journal of Engineering Mechanics Division (ASCE)*, Vol. 102, No. 2, pp. 249-263.
- Westermo, B.D. and Udwadia, F. (1983), "Periodic response of a sliding oscillator system to harmonic excitation", *Earthquake Engineering and Structural Dynamics*, Vol. 11, No.1, pp. 135-147.
- Wolf J.P. (1989), "Soil-structure interaction analysis in time domain", *Nuclear engineering and design*, pp.381-393.
- Zayas, V.A., Low, S.S. and Mahin, S.A. (1990), "A Simple pendulum technique for achieving seismic isolation", *Earthquake Spectra*, Vol. 6, No 2, pp.317-333.

Relevant Codes

- IS 1343: 1980, "Code of Practice for Prestressed Concrete," First Revision, Indian Standard, New Delhi, India.
- IS 13920-1993, "Code of practice for ductile detailing of RC structures", Bureau of Indian Standards, New Delhi, India.
- IS 1893:1984, "Criteria for Earthquake Resistant Design of Structures", Bureau of Indian Standards, New Delhi, India.
- IS 1893:2002, "Criteria for Earthquake Resistant Design of Structures", Part-1 General provisions and Buildings, Bureau of Indian Standards, New Delhi, India.
- IS 456:2000, "Plain and Reinforced Concrete - Code of Practice," Fourth Revision, Indian Standard, New Delhi, India.

Websites

AERB (2008), “Seismic safety of nuclear power plants” – *A Monograph, Atomic Energy Regulatory Board*, available from www.aerb.gov.in.

<http://earthquake.usgs.gov>

<http://facstaff.gpc.edu/~pgore/Earth&Space/images/Fig4.gif>

<http://pubs.usgs.gov/of/1996/ofr-96-0263/localeff.htm>

<http://www.pbs.org/gbh/aso/tryit/tectonics/intro.html>

http://www.portal.gsi.gov.in/gsiDoc/pub/cs_sumatra.pdf

<http://www.tulane.edu/~sanelson/geol204/struct&materials.htm>

<http://www.vibrationdata.com/elcentro.dat>

MCEER, Multi-Disciplinary Center for Earthquake Engineering Research
<http://mceer.buffalo.edu>

Miura, K. (2011). “Dynamic soil structure interaction,” IISEE-UNESCO lecture notes from web site <http://iisee.kenken.go.jp/lna/?mod=view&cid=E0-190-2008#>

Murthy, C.V.R., “Earthquake tips, Learning earthquake design and construction”, Building material and technology promotion council, Government of India, New Delhi, 2005. Available from http://www.ourvmc.org/Files/EQTips_Full.pdf

NICEE website, <http://www.nicee.org>

Science Learn, <http://www.sciencelearn.org.nz/Contexts/Earthquakes/Sci-Media/Images/Bhuj-Hospital>